

MATERIALS USED

STRAPS:

The straps are made of high tenacity filaments that provide greater resistance than conventional filaments. The textile material is resistant to surface flame (class F2 / 1,5 mm) and to end flame (class K2 / 1,5mm).

FOAM:

The legs and waist straps are protected with progressive density foam (reticulated cell polyethylene) that provides greater comfort, breathability and avoids moisture buildup.

THREADS:

100% polyamide threads that offers good resistance to friction and other aggressions. In contrast colors to ribbons for better viewing and inspection.

BUCKLES:

Made of stamped stainless steel, no seams or welds that allow greater resistance to saline environments and humidity.

contact:

@no.ar.danca.aerea

(11) 99448-1709

no.ar.danca.aerea@gmail.com

www.noardancaaerea.com

NO AR

MANUAL - harness

VENTO KIDS

CADVENK1 – 4 to 8 years old – 58 to 68 waist - orange

CADVENK2 – 9 to 12 years old – 68 to 88 waist - blue

The VENTO Kids harness has been specially designed for use of children for the Bungee Exercises mode.

It attends to the most demanding and precise movements, without losing something essential: comfort.

It allows 3 types of anchoring: frontal, lateral and posterior.

The double lateral anchor is obtained by removing the 40 cm side tapes that accompany the product.

This product has a new safety limiting system, created exclusively by NO AR, in order to facilitate the waist regulation.



Vento Kids - frontal view



Vento Kids - rear view

THIS PRODUCT IS NOT TO BE USED FOR CLIMBING ACTIVITIES

HOW TO DRESS UP YOUR VENTO KIDS



1. As you remove the VENTO Kids from its packaging and check that all its adjustments are practically at their maximum opening limit to facilitate their placement, position it in the best way to insert the legs.



2. After positioning, take it your hips and adjust the rear adjustable strap, pulling on its end.



3. Proceed by slightly regulating the leg straps, one at a time, so that the stroller is firm and comfortable.



4. Proceed by slightly regulating the the other leg strap, so that the stroller is firm and comfortable.



5. To use the front anchor, connect the extensor carabiner to the waist ventral handle.



6.For the rear anchorage, connect the bungee carabiner with the side straps.



7. To be able to practice Double Bungee using two bungees, use the lateral straps of the harness, leaving them aligned with the iliac bones.

NO AR

GENERAL INFORMATION

This Technical Manual provides essential instructions for the proper use and maintenance of the **VENTO KIDS** model harness. It is important to emphasize that a specific previous training is essential for the use of this product.

Temperature:

This product must be used at a temperature between -40 C° and +80 C°.

Cuts and abrasion:

Avoid friction on abrasive surfaces and sharp edges during use.

Chemical products :

All chemical products, corrosive materials and solvents can be dangerous, because they can suffer a reaction with the raw material of the product.

In case of doubts, get in touch with our technical department.

Exposure to UV rays:

Despite the high resistance of polyester to the action of UV rays, it is recommended not to leave this product exposed to sun light for a long time.

NO AR

EVALUATION OF HARNESS INTEGRITY

Inspection:

For greater safety and control of your harness, we recommend that an inspection sheet be drawn up for each product.

This inspection must understand:

- Seams: attention to loose or worn threads.
- Straps: attention to possible cuts, abrasion wear, damage caused by use, heat, chemicals, etc.
- Color: check the possible loss of the color of the straps, being able to be a determining reason for the discarding of the product.
- Metal parts: despite being manufactured in stainless steel, attention to possible points of oxidation wear or cracks.

STORAGE AND TRANSPORT:

During transportation and storage, observe the following conditions:

- Keep these harnesses in their original packaging or in bags other than the pond type.
- Cleansed.
- Dry.
- In an airy place.
- Under room temperature,
- Protected from the sun or direct sources of light.
- Protected from corrosive or aggressive substances.
- Far from the ground, mainly cement.

We recommend that inspections be carried out **PERIODICALLY**

CLEANING AND HYGIENIZATION:

Inspection:

To conserve your product and maintain its useful life, we recommend that you always wash your equipment and especially if it was used near aggressive environments.

Excessive transpiration of the body can also gradually compromise the metal parts.

This is a reason for it to be washed periodically.

Cleaning:

Textile products should be washed and rinsed by hand only with clean and abundant water (maximum temperature of 30 ° C) and with a soft brush, if necessary.

Drying:

In the final phase of drying, a clean white cloth (without any chemical interference) can be used to remove excess water and then allow it to dry slowly in the shade in a well-ventilated place.

MAINTENANCE, MODIFICATION OR ALTERATION:

Any modifications, alterations or repairs without the consent of the manufacturer are totally forbidden, implying the cancellation of the guarantee and the excension of the responsibility of the company on the product.

PRODUCT USEFUL LIFE:

The unused life time is 7 years from the date of manufacture for textile products and metal components. The useful life of a product is the term that expresses the period in which this product maintains its physical and mechanical characteristics without considering any type of wear or use.

Severe or low maintenance wear can limit this service life

GUARANTEE:

This product is guaranteed for six months against any manufacturing defect.

Are excluded from this guarantee:

- Normal wear.
- Modifications or alterations.
- Bad stored.
- Lack of maintenance or cleaning.
- Use for another use to which the product was not intended.